

Lane/5000

Boost NFC acceptance and enhance checkout experience



- Enhance the purchasing experience by combining a large touchscreen display within a compact consumer-facing terminal
- Accelerate checkout offering electronic signature and boosting NFC acceptance
- Leverage a terminal designed for the most demanding retail environments

ingenico



Designed for speed and efficiency, the Lane/5000 boosts NFC acceptance.



All payment methods accepted including QR code payment thanks to an optional camera.

Designed for an intensive use & fast checkout in retail:

- Capacitive screen
- Heavy duty magnetic stripe
- Smartcard readers optimized to boost transaction speeds
- Clear contactless zone


3.5" color touchscreen and ergonomic interface

Highest security:

- PCI PTS
- Optional PCI compliant privacy shield
- Detection of abnormal cable removal to alert and inhibit the terminal in the case of threat
- Anti-theft Kensington lock

Supported by Ingenico's suite of services

- Fleet management & security solutions
- Hardware services
- Professional services



Processor	• Crypto & Crypto Processor	• Cortex A5	✓
Memory	• Internal • External	• 512 MB Flash, 512 MB RAM • Micro SD up to 32 GB	✓ Option
OS		• Telium TETRA	✓
SAM		• 3	Option
Card Reader(s)	• Magstripe • Smart Card • Contactless	• ISO 1/2/3, 500K lifespan • Dual Head • EMV Level 1, 500K lifespan • EMV Level 1 compliant, Felica	✓ Option ✓ ✓
Display	• Colour	• 3.5" backlight, QVGA (320×240 pixels)	✓
Touchscreen	• Resistive • Capacitive	• Finger & stylus (300K lifespan signature) • Finger & stylus (1000K lifespan signature)	✓ Option
Keypad		• 15 keys, raised markings, backlit	✓
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	✓ Option Option
Video	Video accelerator	• H264 codec	✓
Camera		• 5M pixels autofocus (QR code library embedded)	Option

Terminal Connectivity	• Wired • Wireless	• Ethernet 10/100 base T • Bluetooth Class 2 • Wi-Fi	✓ ✓ ✓
Terminal Connections	USB Serial	• USB Host • 2nd USB Host • USB Slave • 1 RS232	✓ Option ✓ ✓
Power supply	• Powered USB • Powered RS232 • Powered Ethernet • External power supply	• 12V (USB retail) • 12V • PoE 802.3af compliant	✓ ✓ Option Option
Stand Mounting		• Universal Payment Mount	✓
Terminal size		• 189×111×48 mm (7.4×4.3×1.9")	✓
Weight		• 350 g (12.3 oz)	✓
Environment	• Operating temperature • Storage temperature • Relative humidity	• 0 to +50°C (32°F to 122°F) • -20 to +70°C (-4°F to 131°F) • 85% HR at +40°C (104°F)	✓ ✓ ✓
Accessories	• Privacy shield • Stylus kit	• PCI compliant • EPC+ compliant*	✓ Option Option
Security		• PCI PTS 5.x online & offline certified	✓

* This locally compliant pinshield is not PCI certified, it is used where local regulations overruled PCI

