# Link/2500

Your smart, sleek and simple payments solution







# The Link/2500 brings payment acceptance solution to any mobile business.



Pocket-sized, light weight and robust design, the Link/2500 is the perfect business acceptance point

#### Payments anywhere and anytime

• 4G, 3G, GPRS, Dual SIM, Bluetooth and WiFi

# Raising the bar on security with PCI PTS compliancy

#### Designed for accessibility:

- Integrated speaker which could provide vocal assistance
- Real mechanical keypad with raised marking

# Multiple alternative payment methods supported


 EMV Chip & PIN, contactless, magstripe or digital wallets

### Optimized battery for a long business day on the go (up to 1200mAh)

#### Supported by Ingenico's suite of services

- Fleet management & security solutions
- Hardware services
- Professional services





|                         |  |  | LINK/<br>2500 | LINK/<br>2500<br>TOUCH |
|-------------------------|--|--|---------------|------------------------|
| Processor               | Application     Crypto processor         | • Cortex A5  | •             | V                      |
| Memory                  | • Internal                               | • 256 MB Flash,<br>128 MB RAM<br>• 128 MB Flash,<br>128 MB RAM                   | Option        | Option                 |
| os                      |  | Telium TETRA   | V             | V                      |
| SIM / SAM               |  | • Up to 2  | Option        |                        |
| Card readers            | Magstripe     Smart card     Contactless | • ISO 1/2/3, 500K lifespan<br>• EMV Level 1,<br>50K lifespan<br>• EMV / iSO14443 | <b>⋄</b>      | <b>⋄</b>               |
| Display                 | • Colour                                 | • 2.4" colour display, backlit,<br>QVGA (240×320 pixels)                         | <b>✓</b>      | <b>✓</b>               |
| Keypad                  | Mechanical                               | 20 keys, raised marking     Backlighted keypad                                   | ✓<br>N/A      | Option                 |
| Audio                   | Buzzer     Speaker                       |  | Option        | Option                 |
| Terminal<br>connections | • USB Type C                             | Host & Slave   | <b>⋄</b>      | <b>✓</b>               |

|                       |                                  |  | LINK/<br>2500    | LINK/<br>2500<br>TOUCH |
|-----------------------|----------------------------------|--|------------------|------------------------|
| Terminal connectivity | • WAN                            | 4G and/or 3G with fallback;<br>Dual SIM    | Option           | Option                 |
|                       | • I AN                           | Bluetooth     WiFi (Dual band)             | Option<br>Option | Option<br>Option       |
|                       | - LAIN                           | - Will (Dual ballu)                        | Option           | Option                 |
|                       | Apple IAP Chip     Multicom      | All connectivities<br>in one single device | Option<br>Option | Option                 |
| Terminal size         | • L x W x H                      | • 129 × 70 × 17 mm<br>(5.07 × 2.75 × 0.67) | •                | N/A                    |
|                       |                                  | • 129 × 70 × 18 mm<br>(5.07 × 2.75 × 0.70) | N/A              | ~                      |
| Power<br>supply       | • Terminal                       | • 5V 1A                                    | Option           | Option                 |
| Battery               | • Li-ion                         | • 1200mAh (removable)                      | •                | •                      |
| Weight                | Full featured                    | • 155 q (5.46 oz)                          | <u> </u>         | N/A                    |
|                       |                                  | • 167 g (5.89 oz)                          | N/A              | •                      |
| Environment           | Charging     Temperature         | • 0°C to +40°C<br>(32°F to 104°F)          | V                | •                      |
|                       | Operating     Temperature        | • -10°C to +50°C<br>(-14°F to 122°F)       | ~                | ~                      |
|                       | Storage                          | • -20°C to +55°C<br>(-4°F to 131°F)        | <b>✓</b>         | <b>✓</b>               |
|                       | Temperature • Operating Humidity | • 85% non-condensing at +40°C (104°F)      | <b>✓</b>         | ~                      |
| Accessory             | Cable                            | • USB A to USB C: 1.5m                     | <b>✓</b>         | <b>✓</b>               |
| Security              |                                  | PCI PTS 5.x online     Soffline certified  | <b>✓</b>         | <b>✓</b>               |

