

Desk/2600

Simplicity at the heart of countertop payment



- All payment methods accepted. Optimized for seamless contactless payment
- Save counter space and speed up the checkout process by pairing with the Desk/1600 PIN Pad
- Connect any wired devices through the expansion box enabling a unified integration
- Ensure business continuity with a battery back-up



ingenico



With its nimble design, the Desk/2600 fits perfectly on any counter.



• **Optimized checkout time**

- Multiple alternative payment methods supported
- Highlighted contactless zone
- Large keypad and display
- Paired with the Desk/1600 Pin Pad, saving space and speeding up the checkout

• **Seamless integration with wired POS device**

The expansion box offers wired connectivity options including the Desk/1600 Pin Pad

• **Maximized network availability**

- Ethernet and Wi-Fi
- Battery back-up to cover power loss

• **Highest security**

- PCI PTS v6
- Optional PCI compliant privacy shield
- TETRA vault design provides physical protection of sensitive data

• **Eco design to reduce carbon footprint and control the use of natural resources**

- Usage of components with low power consumption
- Usage of renewable and recycled materials



Processor	• Application & Crypto processor	• Cortex 32bit - 160 Mhz	✓
Memory	• Internal	• 256 MB Flash, 256 MB RAM	✓
OS		• Telium TETRA	✓
Card Reader(s)	• Magnetic card reader • Smart Card • Contactless	• ISO 1/2/3, 500K reads lifespan • EMV L1, 500K reads lifespan • EMV Contactless L1 3.1 spec compliant	✓ ✓ ✓
Display		• 2.8" backlight, glass lens, QVGA (320x240 pixels)	✓
Keypad	• Physical keys	• 15 keys, raised markings, backlit • 4 function keys	✓ ✓
Audio	• Buzzer		✓
Battery	• WAN • Bluetooth	• WIFI w. WPS easy pairing • Bluetooth 4.2 BLE	✓ ✓
Terminal connectivity	• WAN	• WIFI w. WPS easy pairing • 4G / GPRS - Cat1-bis and Cat-M	✓ ✓

Terminal Connections	• USB	• USB-C	✓
Terminal Connections via Accessories	• Expansion Box	• Wired connections - USB-C (device) - USB-C (power) - Ethernet (RJ45) - USB-B (slave) - USB-A (host)	Optional
	• USB peripherals	• RS-232 converter • PSTN modem	Optional
Terminal Size	• Terminal full option without PINshield	• 7.09x3.27x1.69" (180.2x83.2x43 mm)	✓
Terminal Weight	• Terminal only	• 11.29oz (320g)	✓
Environment	• Operating temperature • Storage temperature • Relative humidity	• 32°F to 113°F (0 to +45°C) • -4°F to 131°F (-20 to +70°C) • 85% HR at 104°F (+40°C)	✓ ✓ ✓
Security	• PCI PTS • Privacy shield	• PCI PTS V6 compliant • PCI compliant (factory mounted)	✓ Optional



www.ingenico.com

ingenico