

SELF/7000 & SELF/8000

Ruggedized and secure configurations,
built for outdoor and intensive use cases



- Accepts multiple payment types and complies with the latest standards
- Dual form factors allow for easy retrofit into existing kiosk cutouts
- Reduces vandalism and fraud due to its metal construction and embedded security features
- Provides a user-friendly interface enhancing the customer experience
- Addresses multiple self-service vertical markets

ingenico



The Self/7000 & Self/8000 configuration allows easy and secure integration of cashless payments into self-service solutions, while providing an intuitive consumer experience through an easy-to-use interface.



Ruggedized

Built for outdoor kiosks and designed for intensive use cases, the Self/7000 & Self/8000 configuration is shock and vandalism resistant (IK10 for Self/8000, IK10+ for Self/7000), waterproof (IP65 for Self/8000) and water & dust resistant (IP44 with drainage holes for Self/7000).

Latest Security with PCI PTS v6

The hybrid reader entry mouth is secured by RGB LEDs, metal shutter and a sensor. The PIN entry device includes a presence detector to detect skimmer insertion. Multiple patents contribute to the overall device security.

User friendly

The Self/7000 & Self/8000 configuration is user intuitive because of its color display (adjustable brightness according to ambient light), its presence detector which automatically lights up the keyboard for night time use, card reader LEDs to allow for easier card insertion, and its ability to play WAV files for better voice assisted guidance.

Connected

Self/7000 embeds a full set of connectors (USB, Serial, Sound, LAN) to support multiple use cases. In addition, the optional add-on modules (already available with the Self all-in-one terminals) can extend the terminal capabilities with MDB connectors or wireless connectivity (4G).

Universal

The Self/8000 is compliant with EVA EPSv2 and provides an easy upgrade path from the iUP250. The Self/8000 with the alternative form factor will be able to replace competitive legacy configurations.

Cost-efficiency

Packing a full feature set into a cost efficient design is the goal of the Self/7000 & Self/8000. PCI v6 certification makes commissioning and removal switches for development purposes no longer required.

Flexible

The Self/7000 can be used in a card reader-only configuration for scenarios that do not require a PIN pad.



Self/8000 EVA Form Factor



Self/8000 Artema Form Factor



Self/7000



The Self Series is supported by our Cloud Services

	SELF/8000	SELF/7000
Processor / OS	• Cortex M33 32 bits 160 Mhz (U5) / TETRA	• Cortex M33 32 bits 160 Mhz (U5) / TETRA
Memory	• 786 KB SRAM / 2 MB Flash	• 512 MB Flash, 512 MB RAM • MicroSD up to 32GB
SAM		• 2xSAM ID-000
Contactless reader	• EMV 3.0 Level 1 compliant / ISO 14443 A/B/B'	
Contact reader		• EMV Level 1 / 500k reads lifespan • ISO 1/2/3, 500k reads lifespan • RGB backlit LEDs (anti-skimming)
Display	• 2.5" (320x160) IPS color display (262k colours) • Automatic adjustable light intensity by software and sensor	
Keypad	• 16 metallic keys with RGB keyboard illumination • Proactive overlay/skimmer detection & wake up by presence sensor	
Audio	• Buzzer Monotone	• Buzzer Monotone + polyphonic sound (external speaker)
Terminal connections		• 1x USB Slave (USB-B) • 2x USB Host (USB-A) • 2x RS232 (1x RJ11 + 1x JST) • 1x MDB Master + 1x MDB Slave (optional add-on box)

	SELF/8000	SELF/7000
Terminal connectivity		• 1 x RJ 45 LAN • 4G/LTE +Bluetooth 4.2 BLE (optional add-on module)
Power supply	• 5.5V (thru Self/7000)	• 9-16 V DC • 10-45V (Optional add-on module)
Master/Slave	• Slave unit that must be used with the Self/7000 Master unit	• Master unit that can be deployed with the Self/8000 or in a stand alone card reader only configuration.
IP/IK Rating	• IP65 / IK10	• IP 44 / IK10
Terminal size	• EVA EPS v2 - Standard Door Module (SDM): • 3.9" (W) x 5.2" (H) x 1.6" (D) (100x131.3x40.7mm) • 3.4x4.3" (86.4x108.71mm) • Alternative form factor (compliant with Artema form factor): • 3.9" (W) x 5.6" (H) x 1.6" (D) (100x142.6x40.7mm) • 3.2x4.7" (82.2 x 120.2mm)	• EVA EPS v2: • 4.2" (W) x 2.9" (H) x 5.9" (D) (107 x 73 x 151.1mm) • 2.9x2.4" (74x62mm)
Weight	• 34oz (963g)	• 29oz (825g)
Environment	• -4°F to 158°F (-20°C to +70°C) - Operating • -4°F to 158°F (-20°C to +70°C) - Storage • 95% non-condensing at 131°F (+55°C)	
Security	• PCI PTS 6.x certified	



www.ingenico.com

ingenico