

Lane/3600

Fast, secure and compact PIN Pad solution



- Ensure best-in-class transaction flow with an extensive contactless zone
- Integrate easily with your retail environment thanks to its compact size and wide range of accessories such as standpole and kiosk adaptation plate
- Provide a user-friendly, compact terminal for easy self-checkout



ingenico



With its compact design, the Lane/3600 fits perfectly in any retail or hospitality environment.



Optimized for payment

- All payment methods accepted, one easy-to-identify contactless reader.

Designed for an intensive use in retail

- Powerful processing to increase transaction speed
- Boosted memory (Up to 512MB RAM 256MB FLASH)
- High speed processor (Cortex A7)

Robust device for demanding retail environment

- Display with glass lens
- High-performance card & swipe insertion.

Easy integration into semi-attended kiosks

- With optimized dimension and adaptation plate.

Rear and fast QR code reader integrated camera


- Full-integrated 0.3MP rear camera

Highest security

- PCI PTS v6
- Optional PCI compliant privacy shield
- Detection of abnormal cable's removal to alert and up to inhibit the terminal in case of threats
- Anti-theft Kensington lock

Supported by Ingenico's suite of service

- Fleet management & security solutions
- Hardware services
- Professional services



Processor	• Application & Crypto processor	• Cortex A7	✓
Memory	• Internal	• 256 MB Flash, 256 MB RAM • 256 MB Flash, 512 MB RAM	✓ Option
OS		• Telium TETRA	✓
SAM	• SAM slots	• 1	✓
Card Reader(s)	• Magnetic card reader • Smart Card • Contactless	• ISO 1/2/3 (500K reads lifespan bi-directional swiping) • EMV L1 (500K reads lifespan) • EMV Contactless L1 3.0 spec compliant	✓ ✓ ✓
Integrated Camera		• 0,3M pixels (QR code library embedded)	Option
Display		• 2.8"backlight, glass lens, QVGA (320×240 pixels)	✓
Touchscreen	• Capacitive	• Finger (1000K lifespan signature)	✓
Keypad	• Physical keys	• 15 keys, raised markings, backlit • 4 function keys (non-touch version) • Laser etched	✓ Option Option
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	✓ Option Option

Terminal Connections	• HDMI	• IDMI	✓
Terminal Connections via Accessories	• Ethernet • USB • Serial • Powered USB • Powered RS 232 • Com Box • POE Box • External Power Supply	• Ethernet 10/100 base T • USB Host • USB Slave • 1 RS232 • 5V and 12 V (USB retail) • 12 V • Power over Ethernet Option	✓ ✓ ✓ ✓ ✓ Option Option
Stand Mounting	• Universal Payment Mount		✓
Privacy PIN shield	• Standard privacy shield	• PCI compliant (factory mounted)	Option
Color customisation	• Rear casing		Option
Terminal Size	• Terminal only	• By standard white or black	✓
Terminal Weight	• Terminal full option without PINshield	• 227g (8oz)	✓
Environment	• Operating temperature • Storage temperature • Relative humidity	• 0 to +50°C (32°F to 122°F) • -20 to +70°C (-4°F to 158°F) • 85% HR at +40°C (104°F)	✓ ✓ ✓
Security	• PCI PTS • Anti-removal • Anti-theft	• PCI PTS V6 compliant • Active connector removal • Kensington lock receptacle	✓ ✓ ✓



www.ingenico.com

ingenico