# Lane/7000

Driving sleek, secure and smart checkout experiences



- Engage consumers with a large multimedia touchscreen and user-friendly HTML5 interface
- Quick and easy payment options to improve checkouts
- Integrate simply into any environment
- Help reduce PCI-DSS audit scope with seamless semi-integrated configuration options





### Designed for speed and efficiency, the Lane/7000 creates new points of consumer engagement that improve brand loyalty and drive additional sales.



#### All payment methods accepted including QR code payment thanks to an optional camera

#### Designed for fast checkout in retail:

- Large capacitive screen
- Clear contactless zone
- Large white backlighted keypad
- Payment methods illuminated


#### Large 5" color touchscreen and ergonomic interface

#### Highest security: • PCI PTS

- Optional PCI compliant privacy shield
- Detection of abnormal cable removal to alert and inhibit the terminal in the case of threat
- Anti-theft Kensington lock

#### Supported by Ingenico's suite of services

- Fleet management & security solutions
- Hardware services
- Professional services





_			
Processor	• Crypto & Applications Processor	• Cortex A5	<
Memory	• Internal • External	<ul><li>512 MB Flash, 512 MB RAM</li><li>Micro SD up to 32 GB</li></ul>	<ul> <li>Option</li> </ul>
os		• Telium TETRA HTML5	<
SAM		• 3	Option
Card Reader(s)	<ul> <li>Magstripe (dual head)</li> <li>Smart Card</li> <li>Contactless</li> </ul>	<ul> <li>ISO1/2/3,</li> <li>500K reads lifespan</li> <li>EMV Level 1,</li> <li>500K reads lifespan</li> <li>EMV Contactless L1 3.0 spec compliant</li> </ul>	8 8 8
Display	• Colour	<ul> <li>5' backlight WVGA, TN* display (800×480)</li> <li>5' backlight WVGA, AWVA** display (800×480)</li> </ul>	<ul> <li>✓</li> <li>Option</li> </ul>
Touchscreen	• Capacitive	<ul> <li>Finger &amp; stylus (1000K lifespan signature)</li> </ul>	~
Stylus	• Passive	Tethered included	~
Keypad		• 15 keys, raised markings, backlit	<ul> <li></li> </ul>
Camera		• 5M pixels autofocus (QR code library embedded)	Option
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	✓ Option Option

Terminal Connectivity	• Wired • Wireless	• Ethernet 10/100 base T • Ethernet switch • WIFI and Bluetooth	<ul><li>✓</li><li>Option</li><li>Option</li></ul>
Terminal Connections	USB     Serial     Powered USB     Powered RS 232     Powered Ethernet     External Power Supply	<ul> <li>USB Host</li> <li>2nd USB Host</li> <li>USB Slave</li> <li>1 RS232</li> <li>12 V (USB retail)</li> <li>12 V</li> <li>PoE 802.3af compliant</li> </ul>	♥ Option ♥ ♥ ♥ Option
Stand Mounting		Universal Payment Mount	~
Terminal Size		• 180 × 152 × 35,2 mm (7.44" x 5.89" x 1.38")	<
Weight		• 583g (20,56oz) • 796g (28,08oz)	<
Environment	<ul> <li>Operating temperature</li> <li>Storage temperature</li> <li>Relative humidity</li> </ul>	• 0 to +50°C (32°F to 122°F) • -20 to +70°C (-4°F to 131°F) • 85% HR at +40°C (104°F)	<ul><li></li><li></li><li></li><li></li><!--</th--></ul>
Accessories	<ul> <li>Privacy shield</li> </ul>	• PCI compliant	<
Security	• PCI PTS • Anti-removal • Anti-theft	PCI PTS 6.x and 5.x certified     Active connector removal     Kensington lock receptacles     Secure mounts available	♥ ♥ ♥ Option

\* TN: Twisted Nematics \*\*AWVA: Angle Wide Vertical Aligned to provide a better viewing angle, better color depth and no grey inversion phenomenon



## ingenico