

ingenico

DESK/1600

Smart customer-facing PIN Pad,
for a seamless self-checkout



Speed up the payment
for Desk/series terminals



Manage customer
interface for any type
of payment at the
latest standards



Integrate with any
counter space thanks
to a compact and
nimble design



Connect easily to the
desktop solution thanks
to one single connector



Desk/1600 covers all payment methods and focus on contactless validation. Nimble in design, it takes up a limited space on a potentially busy countertop, resist to intensive sanitization and tapping by contactless cards and NFC smartphones.

Optimized for payment:

- Multiple alternative payment methods supported
- Clear contactless zone
- Large keypad

Easy connectivity to desktop solutions thanks to one single connector

Compact design to fit easily on any counter

Raising the bar on security with PCI PTRS v6

Supported by Ingenico's suite of services



Specifications

OS		• Telium TETRA	
Processor	<ul style="list-style-type: none"> • Application processor • Crypto processor 	• Cortex 32bit -160 MHz	
Memory	• Internal	• 700 KB RAM, 2 MB Flash	
Card readers	<ul style="list-style-type: none"> • Magstripe • Smart card • Contactless 	<ul style="list-style-type: none"> • ISO 1/2/3, 500K lifespan • EMV Level 1, 500K lifespan • EMV Contactless L1 3.0 certified 	
Display	• Color	• 2.8" display, QVGA (320x240 pixels) - Glass lens	
Keypad		• 15 keys, raised marking • 4 function keys	
Terminal connections	• USB	• 1 USB Host	

Audio	• Buzzer		
Terminal size		• 180.2x83.2x43mm (7.08x3.26x1.69")	
Weight		• 221 g (7.79 oz)	
Data capture	<ul style="list-style-type: none"> • Positioning • Rear camera • Scanner 	<ul style="list-style-type: none"> • Tracking GPS, GLONASS, BEIDOU • 5MP, autofocus, flash, code scanning 	
Environment	<ul style="list-style-type: none"> • Operating temperature • Storage temperature • Operating humidity 	<ul style="list-style-type: none"> • -10°C to +50°C (14°F to 122°F) • -20°C to +70°C (-4°F to 158°F) • 10% to 90% non-condensing 	
Accessory	• Privacy shield	<ul style="list-style-type: none"> • Factory mounted • Field upgrade 	Option Option
Security		• PCI PTS 6.x online & offline certified	

