

ingenico

DESK/2600

Simplicity at the heart of countertop payment



All payment methods accepted. Optimized for seamless contactless payment



Save counter space and speed up the checkout process by pairing with the Desk/1600 PIN Pad



Connect any wired devices through the single MagicBox cable enabling a unified integration



Ensure business continuity with a battery back-up



With its nimble design, Desk/2600 fits perfectly on any counter.

Optimized checkout time

- Multiple alternative payment methods supported
- Highlighted contactless zone
- Large keypad and display
- Paired with Desk/1600, saving space and speeding up the checkout

Seamless integration with wired POS device

MagicBox cable offering various wired connectivity including customer module for Desk/1600

Maximized network availability

Ethernet, Wi-Fi and 4G with dual SIM

Highest security

- PCI PTS v6
- Optional PCI certified privacy shield
- Highest physical protection of sensitive data thanks to TETRA vault design

Eco design to reduce carbon footprint and control the use of natural resources

- Usage of components with low power consumption
- Usage of renewable and recycled materials

Supported by Ingenico's suite of services



Specifications

OS		• Telium TETRA	✓
Processor	• Application processor • Crypto processor	• Cortex A7	✓
			✓
Memory	• Internal	• 256 MB Flash, 256 MB RAM	✓
Card readers	• Magnetic card reader • Smart Card • Contactless	• ISO 1/2/3, 500K reads lifespan	✓
		• EMV L1, 500K reads lifespan	✓
		• EMV Contactless L1 3.0 certified	✓
Display		• 2.8" backlight, glass lens, QVGA (320x240 pixels)	✓
Keypad	• Physical keys	• 15 keys, raised markings, backlit	✓
		• 4 function keys	✓
Audio	• Buzzer		✓
Thermal printer	• Speed in l/s • Paper roll cage	• up to 24 l/s	✓
		• 58 mm width x Ø 40 mm	✓
Terminal connectivity	• WAN	• WIFI w. WPS easy pairing • 4G (fallback GPRS) and / or 3G	Option Option

Terminal Connections	• USB	• USB-C	✓
Terminal Connections via Accessories	• Magic Box	• USB-C (device) • USB-C (power) • Ethernet (RJ45) • USB-B (slave) • USB-A (host) • USB-A (option)	Option Option Option Option Option Option
	• USB peripherals	• RS-232 converter • PSTN modem	Option Option
Terminal Size	• Terminal full option without PINshield	• 179x77.4x55 mm (7.04x3.05x2.16")	✓
Terminal Weight	• Terminal only	• 285g (10.05oz)	✓
Environment	• Operating temperature • Storage temperature • Operating humidity	• 0 to +45°C (32°F to 113°F)	✓
		• -20 to +50°C (-4°F to 122°F)	✓
		• 85% HR at +40°C (104°F)	✓
Security	• PCI PTS • Privacy shield	• PCI PTS V6 certified • PCI PTS certified (factory mounted)	✓ ✓

