



# LANE/7000

Driving sleek, secure and smart checkout experiences



Engage consumers with a large multimedia touchscreen and user-friendly HTML5 interface



Quick and easy payment options to improve checkouts



Integrate simply into any counter environment



Help reduce PCI-DSS audit scope with seamless semi-integrated configuration options



# Designed for speed and efficiency, Lane/7000 creates new points of consumer engagement that improve brand loyalty and drive additional sales.

All payment methods accepted including QR code payment thanks to an optional camera.

## Designed for fast checkout in retail:

- Large capacitive screen
- Clear contactless zone
- Large white backlit keypad
- Payment methods illuminated

## Large 5" color touchscreen and ergonomic interface

## Highest security:

- PCI PTS
- Optional PCI PTS certified privacy shield
- Detection of abnormal cable removal to alert and inhibit the terminal in the case of threat
- Secured lock receptacle

## Supported by Ingenico's suite of services



## Specifications

OS		• Telium TETRA, HTML5	
Processor	• Crypto & Applications Processor	• Cortex A5	
Memory	• Internal • External	• 512 MB Flash, 512 MB RAM • Micro SD up to 32 GB	Option
SAM		• 3	Option
Card readers	• Magstripe (dual head) • Smart Card  • Contactless	• ISO1/2/3, 500K reads lifespan • EMV Level 1, 500K reads lifespan • EMV Contactless L1 3.0 certified	
Display	• Color	• 5" backlight WVGA, TN* display (800x480) • 5" backlight WVGA, AWVA** display (800x480)	Option
Touchscreen	• Capacitive	• Finger & stylus (1000K lifespan signature)	
Stylus	• Passive	• Tethered included	
Keypad		• 5 keys, raised markings, backlit	
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	Option Option
Camera		• 5M Pixels autofocus (QR code library embedded)	Option

Terminal Connectivity	• Wired  • Wireless	• Ethernet 10/100 base T • Ethernet switch • WIFI and Bluetooth	Option Option
Terminal Connections	• USB  • Serial • Powered USB • Powered RS 232 • Powered Ethernet • External Power Supply	• USB Host • 2nd USB Host • USB Slave • 1 RS232 • 12 V (USB retail) • 12 V • PoE 802.3af compliant	Option  Option Option
Stand Mounting		• Universal Payment Mount	
Terminal size		• 180 x 152 x 35,2 mm (7,44" x 5,89" x 1,38")	
Weight		• 583g (20,56oz)	
Environment	• Operating temperature • Storage temperature • Operating humidity	• 0 to +50°C (32°F to 122°F) • -20 to +70°C (-4°F to 131°F) • 85% HR at +40°C (104°F)	
Accessory	• Privacy shield	• PCI PTS certified	
Security	• PCI PTS • Anti-removal • Anti-theft	• PCI PTS 6.x certified • Active connector removal • Secured lock receptacle • Secure mounts available	Option

