



LANE/8000


Driving sleek, secure and smart checkout experiences




Engage consumers with a large multimedia touchscreen and user-friendly HTML5 interface


Improve checkouts with quick and easy payment options


Integrate simply into any retail counter


Help reduce PCI-DSS audit scope with seamless semi-integrated configuration options



Designed for speed and efficiency, Lane/8000 creates new points of consumer engagement that improve brand loyalty and drive additional sales.

All payment methods accepted including QR code payment thanks to an optional camera.

Designed for fast checkout in retail:


- X-Large capacitive screen
- Clear contactless zone
- Large white backlighted keypad
- Payment methods illuminated

X-large 7" color touchscreen and ergonomic interface

Highest security:

- PCI PTS
- Optional PCI PTS certified privacy shield
- Detection of abnormal cable removal to alert and inhibit the terminal in the case of threat
- Secured lock receptacle

Supported by Ingenico's suite of services



Specifications

OS		• Telium TETRA, HTML5	
Processor	• Crypto & Applications Processor	• Cortex A5	
Memory	• Internal • External	• 512 MB Flash, 512 MB RAM • Micro SD up to 32 GB	Option
SAM		• 3	Option
Card readers	• Magstripe (dual head) • Smart Card • Contactless	• ISO1/2/3, 500K reads lifespan • EMV Level 1, 500K reads lifespan • EMV Contactless L1 3.0 certified	
Display	• Color	• 7" backlight WVGA, TN* display (800x480)	
Touchscreen	• Capacitive	• Finger & stylus (1000K lifespan signature)	
Stylus	• Passive	• Tethered included	
Keypad		• 5 keys, raised markings, backlit	
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	Option Option
Camera		• 5M Pixels autofocus (QR code library embedded)	Option

Terminal Connectivity	• Wired • Wireless	• Ethernet 10/100 base T • Ethernet switch • WIFI and Bluetooth	Option Option
Terminal Connections	• USB • Serial • Powered USB • Powered RS 232 • Powered Ethernet • External Power Supply	• USB Host • 2nd USB Host • USB Slave • 1 RS232 • 12 V (USB retail) • 12 V • PoE 802.3af compliant	Option Option Option
Stand Mounting		• Universal Payment Mount	
Terminal size		• 200 x 205,5 x 44 mm (7,87" x 8,07" x 1,73")	
Weight		• 796g (28,08oz)	
Environment	• Operating temperature • Storage temperature • Operating humidity	• 0 to +50°C (32°F to 122°F) • -20 to +70°C (-4°F to 131°F) • 85% HR at +40°C (104°F)	
Accessory	• Privacy shield	• PCI PTS certified	
Security	• PCI PTS • Anti-removal • Anti-theft	• PCI PTS 6 certified • Active connector removal • Secured lock receptacle • Secure mounts available	Option

