



LINK/2500 Companion LE

Your smart, sleek and simple payments solution



Accept all payment methods like NFC/Contactless, Apple Pay and Samsung Pay for more flexibility



Create mobile point of sales anywhere with a slim and robust device.



Leverage TELIUM applications for reduced time-to-market



Ensure business continuity with boosted battery



Link/2500 brings payment acceptance solution to any mobile business.

Pocket-sized, light weight and robust design, Link/2500 is the perfect business acceptance point

Payments anywhere and anytime

- Bluetooth and WiFi

Improved power management and boosted battery autonomy thanks to the energy-efficient components

Multiple alternative payment methods supported

- EMV Chip & PIN, contactless, magstripe or digital wallets

Raising the bar on security with PCI PTS certification

Supported by Ingenico's suite of services



Specifications

			Link/2500 Slim	Link/2500 Standard
OS		• Telium TETRA		
Memory	• Internal	• 256 MB RAM / 256 MB Flash		
Card readers	• Contactless • Smart Card • Magstripe	• ISO 1/2/3, 100K lifespan • EMV Level 1, 50K lifespan • EMV Contactless L1 3.1 certified / Support ISO 14443		
SIM/SAM		• up to 2		
Display	• Color	• 2.4" colour display, backlit, QVGA (240x320 pixels)		
Keypad	• Mechanical	• 20 keys, raised marking		
Audio	• Buzzer			
Terminal Connectivity	• LAN • Apple IAP Chip	• Bluetooth • WiFi (Dual band)		N/A

			Link/2500 Slim	Link/2500 Standard
Terminal Connections	• USB Type C	• Host & Slave (3K insertions)		
Terminal size	• L x W x H	• 129 x 70 x 13 mm (5.07 x 2.75 x 0.51") • 129 x 70 x 17 mm (5.07 x 2.75 x 0.67")		N/A
Power supply	• Terminal	• 5V 1A		Option
Batteries	• Li-ion	• 1200mAH (removable) • 600mAH		N/A
Weight	• Full featured	• 120g (4.23oz) • 155g (5.46oz)		N/A
Security		• PCI PTS 6.x online & offline certified		
Environment	• Charging Temperature • Operating Temperature • Storage Temperature • Operating Humidity	• 0°C to +40°C (32°F to 104°F) • -10°C to +50°C (14°F to 122°F) • -20 to +55°C (-4°F to 131°F) • 85% non-condensing at 40°C (104°F)		
Accessories	• Cable	• USB A to USB C: 1.5m		

