


LINK/2500 Integration LE

Clever payment companion designed with integration in mind



Accept all payment methods like NFC/Contactless, Apple Pay and Samsung Pay for more flexibility



Facilitate the integration with a third-party device



Leverage TELIUM applications for reduced time-to-market



Ensure business continuity with boosted battery



Link/2500 Integration LE brings payment acceptance anywhere in the store.

Paired with any iOS, Android or Windows-based tablet or smartphone to accept payment anywhere, anytime

Designed for integration: lightweight, slim design, as well as mechanical and electronic integration to charge and communicate with a third-party device

Power management improved and battery autonomy boosted thanks to the energy-efficient components

Compact yet robust

Raising the bar on security with PCI PTS compliancy

Supported by Ingenico's suite of services



Specifications

OS		<ul style="list-style-type: none"> Telium TETRA
Processor	<ul style="list-style-type: none"> Application processor Crypto processor 	<ul style="list-style-type: none"> Cortex A7
Memory	<ul style="list-style-type: none"> Internal 	<ul style="list-style-type: none"> 256 MB Flash, 256 MB RAM
Card readers	<ul style="list-style-type: none"> Magstripe Smart card Contactless 	<ul style="list-style-type: none"> ISO 1/2/3, 100K lifespan EMV Level 1, 50K lifespan EMV / ISO14443
Display	<ul style="list-style-type: none"> Color 	<ul style="list-style-type: none"> 2.4" colour display, backlit, QVGA (240x320 pixels)
Keypad	<ul style="list-style-type: none"> Mechanical 	<ul style="list-style-type: none"> 20 keys, raised marking
Audio	<ul style="list-style-type: none"> Buzzer 	

Terminal Connectivity	<ul style="list-style-type: none"> LAN Apple IAP Chip LAN Apple IAP Chip 	<ul style="list-style-type: none"> Bluetooth Back connector for charging & USB data exchange Certified MFI in BT & USB
Terminal size	<ul style="list-style-type: none"> L x W x H 	<ul style="list-style-type: none"> 129x70x13 mm (5.07x2.75x0.51")
Battery	<ul style="list-style-type: none"> Li-ion 	<ul style="list-style-type: none"> 600mAh
Weight	<ul style="list-style-type: none"> Full featured 	<ul style="list-style-type: none"> 120 g (5.46 oz)
Security		<ul style="list-style-type: none"> PCI PTS 6.x online & offline certified
Environment	<ul style="list-style-type: none"> Charging Temperature Operating Temperature Storage Temperature Operating Humidity 	<ul style="list-style-type: none"> 0°C to +40°C (32°F to 104°F) -10°C to +50°C (14°F to 122°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C (104°F)

