


ingenico

MOVE/2600

Ensure payments on the move,
safely and fastly



All payment methods accepted. Optimized for seamless contactless payment



Terminals' functionality insured with excellent connectivity and long-lasting battery



Robust, affordable and functional device to meet merchants' daily needs



Top-level security with PCI PTS V6 and contactless EMV v3 certification



The Move/2600, perfect for grab-and-go use.

Optimized checkout time

- Multiple alternative payment methods supported
- Highlighted contactless zone
- Large keypad and display

Compact yet powerful, designed to address in-store and on-the-move payment

Payment anywhere and anytime

- Wi-Fi and 4G with fallback to 2G and or 3G

Eco design to reduce carbon footprint and control the use of natural resources

- Use of components with low power consumption
- Use of renewable and recycled materials

Highest security

- PCI PTS v6
- Optional PCI PTS certified privacy shield
- Highest physical protection of sensitive data thanks to TETRA vault design

Optimized autonomy, to handle business all day long

Supported by Ingenico's suite of services



Specifications

OS		• Telium TETRA	✓
Processor	• Application processor • Crypto processor	• Cortex A7	✓
			✓
Memory	• Internal	• 256 MB Flash, 256 MB RAM	✓
		• 512 MB Flash, 256 MB RAM	Option
Card readers	• Magnetic card reader • Smart Card • Contactless	• ISO 1/2/3, 500K reads lifespan	✓
		• EMV L1, 500K reads lifespan	✓
		• EMV Contactless L1 3.0 spec compliant	✓
SIM		• 2 SIM	Option
SAM		• 1 SAM • 2nd and 3rd SAM	✓ Option
Display	• Color	• 2.4"backlit, TFT, 264k (320x240 pixels)	✓
Keypad	• Physical keys	• 15 keys, raised markings, backlit • 5 functional keys without backlight	✓
Terminal printer	• Speed in lines/s • Paper roll cage	• up to 24 lines/s	✓
		• 58mm width x 40mm	

Audio		• Buzzer	✓
Terminal Connectivity	• WAN • LAN	• 4G (fallback GPRS only) and/or 3G	Option
		• WiFi	Option
Terminal Connections	• 1 USB • Power supply	• USB-C	✓
		• via USB-C	Option
Terminal size	• Terminal full option without PINshield	• 167x76x56 mm (6.6x3x2.2")	✓
Battery	• Li-ion	• 2250mAh	✓
Terminal weight	• Terminal and battery	• 295g (10.41oz)	✓
Environment	• Operating temperature • Storage temperature • Operating humidity	• -10°C to +50°C (14°F to 122°F)	✓
		• -20°C to +70°C (-4°F to 158°F)	✓
		• 10% to 90% non-condensing	✓
Security	• PCI PTS • Privacy shield	• PCI PTS V6 certified	✓
		• PCI PTS certified (factory mounted)	Option

