


LANE/3600


Fast, secure and compact PIN Pad solution




Ensure best-in-class transaction flow with an extensive contactless zone



Respond to intensive use with a robust design



Provide a user-friendly, compact terminal for easy self-checkout



Integrate into semi-attended kiosks with optimized dimension and adaptation plate



With its compact design, Lane/3600 fits perfectly in any retail or hospitality environment.

Optimized for payment

- All payment methods accepted, one easy-to-identify contactless reader.

Designed for an intensive use in retail

- Powerful processing to increase transaction speed
- Boosted memory (Up to 512MB RAM 256MB FLASH)
- High speed processor (Cortex A7)

Robust device for demanding retail environment

- Display with glass lens
- High-performance card & swipe insertion.

Easy integration into semi-attended kiosks with optimized dimension and adaptation plate.

Rear and fast QR code reader integrated camera

- Full-integrated 0.3MP rear camera

Highest security

- PCI PTS v6
- Optional PCI PTS certified privacy shield
- Detection of abnormal cable's removal to alert and up to inhibit the terminal in case of threats

Secured lock receptacle

Supported by Ingenico's suite of services



Specifications

OS		• Telium TETRA	✓
Processor	• Application processor • Crypto processor	• Cortex A7	✓
Memory	• Internal	• 256 MB Flash, 256 MB RAM • 256 MB Flash, 512 MB RAM	✓ Option
SAM	• SAM slots	• 1	✓
Card readers	• Magnetic card reader • Smart Card • Contactless	• ISO 1/2/3 (500K reads lifespan bi-directional swiping) • EMV L1 (500K reads lifespan) • EMV Contactless L1 3.0 certified	✓ ✓ ✓
Touchscreen	• Capacitive	• Finger (1000K lifespan signature)	Option
Display		• 2.8" backlight, glass lens, QVGA (320x240 pixels)	✓
Keypad	• Physical keys	• 15 keys, raised markings, backlit • 4 function keys (non-touch version) • Laser etched	✓ Option Option
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	✓ Option Option
Security	• PCI PTS • Anti-removal • Anti-theft	• PCI PTS 6 certified • Active connector removal • Secured lock receptacle	✓ ✓ ✓

Terminal connectivity		• IDMI port	✓
Terminal Connections via Accessories	• Ethernet • USB • Serial • Powered USB • Powered RS 232 • Com Box • POE Box • External Power Supply Ethernet	• Ethernet 10/100 base T • USB Host & USB Slave • 1 RS232 • 5V and 12 V (USB retail) • 12 V • Power over Ethernet Option	✓ ✓ ✓ ✓ Option Option Option
Stand Mounting	• Universal Payment Mount	• PCI PTS certified (factory mounted)	✓
Terminal Size	• Terminal only	• 167x82x40 mm (6.6x3.2x1.6")	✓
Terminal Weight	• Terminal full option without PINshield	• 227g (8oz)	✓
Environment	• Operating temperature • Storage temperature • Operating humidity	• 0 to +45°C (32°F to 113°F) • -20 to +55°C (-4°F to 131°F) • 85% HR at +40°C (104°F)	✓ ✓ ✓
Accessories	• Height privacy shield • POE Box	• BITS pinshield • Power over Ethernet	Option Option

